

The laser one-step and self-weeding transfer paper solution for white and light colored garments.

Feel free to style!

characteristics

### self-weeding · one-step process · different garments



is self-weeding and there is no need to trim the paper. The transfer paper works on various garments like cotton, cotton blends, 100% polyester and leather. Save production costs and time by using Free Style instead of screen printing and flex foils. The possibilities are almost unlimited.

copy and print features

#### for fuser oil-based & oil-free printers and copiers



runs without exception on all color copiers and printers which use fuser oil and most of oil-free machines.

## easy handling · brilliant & soft hand



is designed to transfer isolated full color graphics, letters and numbers without trimming the paper. It only needs one step to transfer the image onto the garment. Free Style offers brilliant colors and soft hand without leaving any background coating film. For transferring square pictures we recommend to use Trans Royal max or Trans Royal inneo.

durability

#### high washability



offers high durability with no loss of color after washing the fabrics several times.

specifications

or 165°C · 330°F for 30 Sec 170°C · 340°F for 25 Sec medium/high pressure

#### always peel after 4-8 sec.

# printing

Cover the image with a silicone or baking paper and press again for 15-30 sec.

priming

Mirror the image

Change printer/copier settings to "Heavy paper mode" Print only onto the coated side (blank)

washing

Max. wash at  $40^{\circ}$ C · Do not tumble dry · Do not bleach · Do not iron the transferred area directly, please cover the image with a baking paper

Temperatures in Fahrenheit and thicknesses in mil are given as approximate values. All data are standard values. The information in this specification sheet is based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customer tests will be required. A legally binding guarantee of specific properties is not to be inferred form our specifications. The information given here may be subject to change without notice.



Joseph-von-Fraunhofer-Str. 3b • 52477 Alsdorf Telefon +49 (0) 24 04-91 99-60/-70 • Telefax +49 (0) 24 04-91 99 18 www.mtct.de • E-Mail: products@mtct.de